

# safety matters

Construction  
Toolbox Talks

From your safety partners at **Crendon Insurance Brokers Ltd**

## Safety Practices While Working on Excavation Sites

Trench collapses are one of the leading causes of injury and death on construction sites. Most of the victims were new employees who lacked training and guidance prior to entering the job site. Sadly, most accidents were preventable.

Whether you are new or a seasoned employee, it is essential that you take the proper precautions to ensure the safety of the entire work crew.

### Protective Systems

The worksite supervisor should inspect the area and determine which protective system will suit the job site and soil most effectively. This is essential, as equipment movement, underground utilities and vibrations can cause a surcharge load on the sides of the trench, forcing it to cave in on the workers inside. The following are the most commonly used protective systems:

- *Sloping*: Protects workers by cutting back the trench wall at an angle inclined away from the excavation
- *Shoring*: Protects workers by installing aluminium hydraulic supports to prevent soil movement

- *Shielding*: Protects workers by using trench boxes to prevent cave-ins
- In addition to one of these three safety measures, a low-traffic zone must be designated around the trench allowing only essential equipment to enter. This will minimise the amount of vibration to which the trench is exposed.

### Avoiding Accidents

Excavation accidents can occur if the underground utilities are not located and removed prior to digging a trench. Once you locate all of the utility lines, label or remove them to prevent injury.

Trench accidents can also happen if safe entrance and exit routes are not present or adequate for the situation. Workers may slip back into the trench as they are trying to climb up a ladder if it is unsupported, placed on a steep slope or is poorly built. To prevent injury while entering and exiting a trench, workers should place the ladder in a trench shield while trying to enter and exit to avoid a cave-in.

**Do not enter a trench without inspecting it at the start of a shift or after a rain shower to ensure that all safety precautions are still in place.**



**Crendon  
Insurance  
Brokers**

The content of this document is of general interest and is not intended to apply to specific circumstances. It does not purport to be a comprehensive analysis of all matters relevant to its subject matter. The content should not, therefore, be regarded as constituting legal advice and not be relied upon as such. In relation to any particular problem which they may have, readers are advised to seek specific advice. Further, the law may have changed since first publication and the reader is cautioned accordingly.

© 2007-13 Zywave, Inc. All rights reserved.