

safety matters

Construction

Toolbox Talks

From your safety partners at **Crendon Insurance Brokers Ltd**

Mounting and Dismounting Equipment

Because jumping down from large equipment is a common practice for construction workers, it's no surprise that lower back, knee, ankle and neck injuries occur frequently. Regardless of the type of equipment that you work with, mounting and dismounting safely should always be top of mind.

What You Can Do

To lessen your risk of injuries, follow these simple mounting and dismounting instructions for lorries and other tall equipment or machinery.

- When using a new piece of machinery, become familiar with the proper mounting and dismounting procedures.
- When a person jumps from a height of more than 30 centimetres, the force that goes through the body is about 14 times the person's body weight. In other words, a 75 kg man who jumps out of a tractor or any other high surface is exerting more than 1,000 kilograms of force on his body. This causes injury to bones, tendons and cartilage. And if you're doing this multiple times every working day, the damage to the body can be extensive.
- When dismounting and mounting, maintain three-point contact. This means having contact with the construction equipment by either one foot and two hands or one hand and two feet. The smaller the triangle you form with your body, the more stable you are.
- Always face the vehicle, both when mounting and dismounting.
- Look at the surface below before stepping and make sure it is even to prevent ankle and knee injuries.
- Never mount or dismount moving equipment.
- Do not mount or dismount with anything, including tools, in your hands. Not only does it throw the body off-balance, it also reduces your chance of recovering your balance if you do slip. Use a drop rope to raise and lower supplies, tools and equipment instead.
- Handholds and footholds are on the equipment for a reason – use them.
- Wear the appropriate clothing. Loose or torn clothing can get caught on equipment when you are jumping down instead of climbing down. In slippery conditions, wear proper footwear to prevent slipping hazards.
- Proper vehicle maintenance also contributes to the safe mounting and dismounting of equipment. Make sure that running boards, treads, steps, footholds and platforms are kept clear. Hazards like ice, snow and grease could cause slips, trips and falls.

To lessen your risk of injury, follow these simple mounting and dismounting instructions for lorries and other construction equipment and machinery.



**Crendon
Insurance
Brokers**

The content of this document is of general interest and is not intended to apply to specific circumstances. It does not purport to be a comprehensive analysis of all matters relevant to its subject matter. The content should not, therefore, be regarded as constituting legal advice and not be relied upon as such. In relation to any particular problem which they may have, readers are advised to seek specific advice. Further, the law may have changed since first publication and the reader is cautioned accordingly.

© 2010-13 Zywave, Inc. All rights reserved.